

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Shell FuelSave Super 95  
Product code : 002D1880

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Fuel for spark ignition engines designed to run on unleaded fuel.  
Please refer to Ch16 for the registered uses under REACH.

Uses advised against : This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier., This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser., This product is designed only to suit automotive applications and no provision is made for the requirements of aviation applications.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : **Shell Deutschland Oil GmbH**  
Suhrenkamp 71-77  
D-22335 Hamburg  
Telephone : (+49) 40 6324-6255  
Telefax : (+49) 40 6321-051  
Email Contact for Safety Data Sheet : If you have any enquiries about the content of this SDS please email [fuelSDS@shell.com](mailto:fuelSDS@shell.com)

#### 1.4 Emergency telephone number

: (+49) 30 3068 6790 (Giftnotruf Berlin)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids , Category 1	H224: Extremely flammable liquid and vapour.
Skin corrosion/irritation , Category 2	H315: Causes skin irritation.
Aspiration hazard , Category 1	H304: May be fatal if swallowed and enters airways.
Reproductive toxicity , Category 2	H361: Suspected of damaging fertility or the unborn child.
Germ cell mutagenicity , Category 1B	H340: May cause genetic defects.
Carcinogenicity , Category 1B	H350: May cause cancer.
Specific target organ toxicity - single	H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

exposure , Category 3, Inhalation,  
Narcotic effects

Chronic aquatic toxicity , Category 2

H411: Toxic to aquatic life with long lasting effects.

### Classification (67/548/EEC, 1999/45/EC)

F+: Extremely flammable

R12: Extremely flammable.

Carc.Cat.2: Carcinogenic Category 2

R45: May cause cancer.

Mut.Cat.2: Mutagenic Category 2

R46: May cause heritable genetic damage.

Xi: Irritant

R38: Irritating to skin.

Xn: Harmful

R63: Possible risk of harm to the unborn child.

Xn: Harmful

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

N: Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H224

PHYSICAL HAZARDS:

Extremely flammable liquid and vapour.

H304

HEALTH HAZARDS:

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness.

H340

May cause genetic defects.

H361

Suspected of damaging fertility or the unborn child.

H350

May cause cancer.

H411

ENVIRONMENTAL HAZARDS:

Toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P201

Obtain special instructions before use.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
<b>Response:</b> P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
<b>Storage:</b> P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
<b>Disposal:</b> P501	Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Moderately irritating to eyes.

Slightly irritating to respiratory system.

A component or components of this material may cause cancer.

This product contains benzene which may cause leukaemia (AML - acute myelogenous leukaemia). May cause MDS (Myelodysplastic Syndrome).

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons (including benzene at 1.0%v/v maximum), with carbon numbers predominantly in the C4 to C12 range.

Contains oxygenated hydrocarbons which may include methyl tertiary butyl ether (MTBE) and other ethers.  
May also contain several additives at <0.1% v/v each.

### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Gasoline, low boiling		F+; R12	Flam. Liq.1; H224	0 - 100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

point naphtha	289-220-8 / 01-2119471335-39	Xn; R65 Mut.Cat.2; R46 Carc.Cat.2; R45 Xi; R38 R67 N; R51/53	Asp. Tox.1; H304 Muta.1B; H340 Carc.1B; H350 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361 Aquatic Chronic2; H411	
Ethyl tertiary butyl ether	637-92-3 211-309-7 / 01-2119452785-29	F; R11 Xi; R38	Flam. Liq.2; H225 Skin Irrit.2; H315	0 - 15
tert-butyl methyl ether	1634-04-4 216-653-1 / 01-2119452786-27	F; R11 Xi; R36/38	Flam. Liq.2; H225 2; H315	0 - 15
Etherified Light Cracked Naphtha	4644-90-0 / 01-0000019579-54	F+; R12 Carc.Cat.2; R45 Mut.Cat.2; R46 Repr.Cat.3; R63 Xn; R48/20/21/22 Xi; R38 Xn; R65 R67 N; R51/53	Flam. Liq.1; H224 Carc.1B; H350 Muta.1B; H340 Repr.2; H361 STOT RE2; H373 Skin Irrit.2; H315 Asp. Tox.1; H304 STOT SE3; H336 Aquatic Chronic2; H411	0 - 35
2-methoxy-2-methylbutane	994-05-8 213-611-4 / 01-2119453236-41	F; R11 Xn; R22 R67	Flam. Liq.2; H225 Acute Tox.4; H302 STOT SE3; H336	0 - 22

Remarks : Dyes and markers can be used to indicate tax status and prevent fraud.

For explanation of abbreviations see section 16.

### Further information

Contains:

Chemical Name	Identification number	Concentration [%]
Xylene, mixed isomers	1330-20-7, 215-535-7	5 - 25
Toluene	108-88-3, 203-625-9	5 - 25
n-Hexane	110-54-3, 203-777-6	0 - 0,5
Naphthalene	91-20-3, 202-049-5	0 - 0,5
cyclohexane	110-82-7, 203-806-2	1 - 5
Cumene	98-82-8, 202-704-5	0 - 0,5
Ethylbenzene	100-41-4, 202-849-4	1 - 5
benzene	71-43-2, 200-753-7	0 - 1
Trimethylbenzene, all isomers	25551-13-7, 247-099-9	0 - 5

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

appropriate personal protective equipment according to the incident, injury and surroundings.

- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.  
When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
- In case of eye contact : Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist transport to the nearest medical facility for additional treatment.
- If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.  
Eye irritation signs and symptoms may include a burning sensation and a temporary redness of the eye.  
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
The onset of respiratory symptoms may be delayed for several hours after exposure.  
Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.  
Auditory system effects may include temporary hearing loss and/or ringing in the ears.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire., Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Clear fire area of all non-emergency personnel.  
If the fire cannot be extinguished the only course of action is to evacuate immediately.  
Keep adjacent containers cool by spraying with water.  
If possible remove containers from the danger zone.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : 6.1.1 For non emergency personnel:  
Do not breathe fumes, vapor.  
Do not operate electrical equipment.  
6.1.2 For emergency responders:  
Shut off leaks, if possible without personal risks.  
Remove all possible sources of ignition in the surrounding area.  
Evacuate all personnel.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Attempt to disperse the vapour or to direct its flow to a safe location, for example by using fog sprays.  
Vapour can travel for considerable distances both above and below the ground surface. Underground services (drains, pipelines, cable ducts) can provide preferential flow paths.

### 6.2 Environmental precautions

Environmental precautions : Take measures to minimise the effects on groundwater.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.  
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Take precautionary measures against static discharges.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
Avoid contact with skin, eyes and clothing.  
Evacuate the area of all non-essential personnel.  
Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.  
Take precautionary measures against static discharges.  
Ensure electrical continuity by bonding and grounding (earthing) all equipment.  
Observe all relevant local and international regulations.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.,  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.,  
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet., Local authorities should be advised if significant spillages cannot be contained., Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26., If contamination of site occurs remediation may require specialist advice.  
To the extent that this product, including its chemical components (e.g. Methyl tertiary butyl ether) may impact surface or groundwater, appropriate assessment and remediation (if necessary) should be implemented.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### SECTION 7: Handling and storage

- General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
- Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Air-dry contaminated clothing in a well-ventilated area before laundering.
- Prevent spillages.
- Turn off all battery operated portable electronic devices (examples include: cellular phones, pagers and CD players) before operating gasoline pump.
- Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.
- Do not use as a cleaning solvent or other non-motor fuel uses.
- Ensure that all local regulations regarding handling and storage facilities are followed.
- Vehicle fueling and vehicle workshop areas - Avoid inhalation of vapours and contact with skin, when filling or emptying a vehicle.

#### 7.1 Precautions for safe handling

- Advice on safe handling : Ensure that all local regulations regarding handling and storage facilities are followed.
- When using do not eat or drink.
- Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
- Never siphon by mouth.
- The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Avoid exposure.
- Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
- Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

- Product Transfer : Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling ( for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Fire-fighting class : Fire hazard classification:  
B

### 7.2 Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510) : 3, Flammable liquids

Other data : Drum and small container storage: Keep containers closed when not in use. Drums should be stacked to a maximum of 3 high. Use properly labeled and closable containers. Packaged product must be kept tightly closed and stored in a diked (bunded) well-ventilated area, away from, ignition sources and other sources of heat. Take suitable precautions when opening sealed containers, as pressure can build up during storage. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., Aluminium may also be used for applications where it does not present an unnecessary fire hazard., Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product., For container linings, use amine-adduct cured epoxy paint., For seals and gaskets use: graphite, PTFE, Viton A, Viton B.
- Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene., However, some may be suitable for glove materials.

- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. Gasoline containers must not be used for storage of other products.

### 7.3 Specific end use(s)

- Specific use(s) : Please refer to Ch16 and/or the annexes for the registered uses under REACH.

Ensure that all local regulations regarding handling and storage facilities are followed.  
See additional references that provide safe handling practices for liquids that are determined to be static accumulators:  
American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Toluene	108-88-3	TWA	50 ppm 192 mg/m <sup>3</sup>	2006/15/EC

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Toluene	108-88-3	STEL	100 ppm 384 mg/m3	2006/15/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Toluene	108-88-3	AGW	50 ppm 190 mg/m3	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Toluene	108-88-3	AGW	200 mg/m3	DE TRGS 900
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
cyclohexane	110-82-7	TWA	200 ppm 700 mg/m3	2006/15/EC
Further information	Indicative			
cyclohexane	110-82-7	AGW	200 ppm 700 mg/m3	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible)			
Ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Ethylbenzene	100-41-4	STEL	200 ppm 884 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Ethylbenzene	100-41-4	AGW	20 ppm 88 mg/m3	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Ethylbenzene	100-41-4	AGW	200 mg/m3	DE TRGS 900
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

n-Hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC
Further information	Indicative			
n-Hexane	110-54-3	AGW	50 ppm 180 mg/m3	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
benzene	71-43-2	TWA	1 ppm 3,25 mg/m3	2004/37/EC
Further information	Substantial contribution to the total burden via dermal exposure possible, Skin, Carcinogens or mutagens			
benzene	71-43-2	TWA	0,5 ppm 1,6 ml/m3	Shell Internal Standard (SIS) for 8-12 hour TWA.
benzene	71-43-2	STEL	2,5 ppm 8 ml/m3	
Cumene	98-82-8	TWA	20 ppm 100 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Cumene	98-82-8	STEL	50 ppm 250 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
Cumene	98-82-8	AGW	20 ppm 100 mg/m3	DE TRGS 900
Further information	European Union (The EU has established a limit value: deviations in value and peak limit are possible), Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Naphthalene	91-20-3	TWA	10 ppm 50 mg/m3	91/322/EEC
Further information	Indicative			
Naphthalene	91-20-3	AGW (Vapour and aerosols, inhalable fraction)	0,1 ppm 0,5 mg/m3	DE TRGS 900
Further information	Commission for dangerous substances, Sum of vapor and aerosols., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

tert-butyl methyl ether	1634-04-4	STEL	100 ppm 367 mg/m3	2009/161/EU
Further information	Indicative			
tert-butyl methyl ether	1634-04-4	TWA	50 ppm 183,5 mg/m3	2009/161/EU
Further information	Indicative			
tert-butyl methyl ether	1634-04-4	AGW	50 ppm 180 mg/m3	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Toluene	108-88-3	toluene: 600 µg/l (Blood)	Immediately after exposition or after working hours	TRGS 903 - Biological limit values
Toluene	108-88-3	o-cresol: 1,5 mg/l (Urine)	Immediately after exposition or after working hours, In case of long-term exposition: after more than one shift	TRGS 903 - Biological limit values
cyclohexane	110-82-7	1,2-cyclohexanediol: 150mg/g Creatinine (Urine)	Immediately after exposition or after working hours, In case of long-term exposition: after more than one shift	TRGS 903 - Biological limit values

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 300 mg/l (Urine)	Immediately after exposition or after working hours	TRGS 903 - Biological limit values
n-Hexane	110-54-3	2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	Immediately after exposition or after working hours	TRGS 903 - Biological limit values
benzene	71-43-2	S-Phenylmercapturic acid: 0,025 mg/g Creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH - Biological Exposure Indices (BEI)
benzene	71-43-2	t,t-Muconic acid: 0,5 mg/g Creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH - Biological Exposure Indices (BEI)

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

gasoline : End Use: Workers  
 Exposure routes: Inhalation  
 Value: 840 mg/m<sup>3</sup>/ 8hlong term, local effects  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Value: 640 mg/m<sup>3</sup>/15 minsacute, local effects  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Value: 180 mg/m<sup>3</sup>/ 24hlong term, local effects

benzene : End Use: Workers  
 Exposure routes: Inhalation  
 Value: 3,24 mg/m<sup>3</sup>/ 8hlong term, systemic effects

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### 8.2 Exposure controls

**Engineering measures** Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Firewater monitors and deluge systems are recommended.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

General Information:

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Do not ingest. If swallowed then seek immediate medical assistance

#### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Eye protection : Wear goggles for use against liquids and gas.  
If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.

Approved to EU Standard EN166.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Hand protection

Remarks

: Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

Skin and body protection

: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.

Protective clothing approved to EU Standard EN14605.

Respiratory protection

: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. All respiratory protection equipment and use must be in accordance with local regulations.

Select a filter suitable for combined particulate/organic gases and vapors [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Thermal hazards : Not applicable

### Environmental exposure controls

General advice : Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.  
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.  
Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : Pale straw

Odour : Hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

Melting point/freezing point : Data not available  
: 25 - 220 °C Method: Unspecified

Flash point : <= -40 °C  
Method: Unspecified

Evaporation rate : Data not available

Flammability (solid, gas) : Not applicable

Upper explosion limit : 8 %(V)

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Lower explosion limit	: 1 %(V)
Vapour pressure	: 30 - 90 kPa (38,0 °C) Method: Unspecified
	50 - 160 kPa (50,0 °C) Method: Unspecified
Relative density	: Data not available
Density	: Typical 745 kg/m <sup>3</sup> (15,0 °C) Method: Unspecified
Solubility(ies)	
Water solubility	: Data not available
Partition coefficient: n-octanol/water	: log Pow: 2 - 7
Auto-ignition temperature	: > 250 °C
Decomposition temperature	: Data not available
Viscosity	
Viscosity, kinematic	: 0,25 - 0,75 mm <sup>2</sup> /s (40 °C) Method: Unspecified
Explosive properties	: Classification Code: NOT CLASS: Not classified
Oxidizing properties	: Not applicable

### 9.2 Other information

Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
--------------	---

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

May oxidise in the presence of air.

### 10.2 Chemical stability

Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reaction is expected when handled and stored according to provisions.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.  
  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.  
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Basis for assessment : Information given is based on product data, a knowledge of the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD 50 Rat: > 5.000 mg/kg  
Remarks: Low toxicity:

Acute inhalation toxicity : LC 50 Rat: > 5 mg/l

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Exposure time: 4 h  
Remarks: Low toxicity:

Remarks: Based on human experience, breathing of vapours or mists may cause a temporary burning sensation to nose, throat and lungs.

Acute dermal toxicity : LD 50 Rabbit: > 2.000 mg/kg  
Remarks: Low toxicity:

Acute toxicity (other routes of administration) :  
Remarks: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

### Skin corrosion/irritation

**Product:**

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

**Product:**

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

**Product:**

Remarks: Not expected to be a sensitiser.

### Germ cell mutagenicity

**Product:**

: Remarks: Contains Benzene, CAS # 71-43-2., May cause heritable genetic damage

Remarks: Mutagenicity studies on gasoline and gasoline blending streams have shown predominantly negative results.

### Carcinogenicity

**Product:**

Remarks: Contains Benzene, CAS # 71-43-2., Known human carcinogen.

Remarks: Contains Benzene, CAS # 71-43-2., May cause leukaemia (AML - acute myelogenous leukaemia).

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Remarks: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

Remarks: An epidemiology study of more than 18,000 petroleum marketing and distribution workers found no significantly increased risk of death from leukemia, multiple myeloma, or kidney cancer associated with gasoline exposure.

Material	GHS/CLP Carcinogenicity Classification
Gasoline, low boiling point naphtha	Carcinogenicity Category 1B
Ethyl tertiary butyl ether	No carcinogenicity classification.
tert-butyl methyl ether	No carcinogenicity classification.
Etherified Light Cracked Naphtha	Carcinogenicity Category 1B
2-methoxy-2-methylbutane	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Gasoline, low boiling point naphtha	IARC: Group 2B: Possibly carcinogenic to humans

Material	GHS/CLP Carcinogenicity Classification
Xylene, mixed isomers	No carcinogenicity classification.
Toluene	No carcinogenicity classification.
n-Hexane	No carcinogenicity classification.
Naphthalene	Carcinogenicity Category 2
cyclohexane	No carcinogenicity classification.
Cumene	No carcinogenicity classification.
Ethylbenzene	No carcinogenicity classification.
benzene	Carcinogenicity Category 1A
Trimethylbenzene, all isomers	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Toluene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Naphthalene	IARC: Group 2B: Possibly carcinogenic to humans

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

benzene

IARC: Group 1: Carcinogenic to humans

### Reproductive toxicity

**Product:**

:

Remarks: Contains Toluene, CAS # 108-88-3., Causes foetotoxicity at doses which are maternally toxic.

Remarks: Contains n-Hexane, CAS # 110-54-3., May impair fertility at doses which produce other toxic effects.

Remarks: Contains Toluene, CAS # 108-88-3., Many case studies involving abuse during pregnancy indicate that toluene can cause birth defects, growth retardation and learning difficulties.

Remarks: Inhalation of high concentrations of gasoline vapour containing Methyl tertiary butyl ether produced a very low incidence of rare birth defects (ventral midline closure failure) in mice.

### STOT - single exposure

**Product:**

Remarks: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

### STOT - repeated exposure

**Product:**

Remarks: Kidney: caused kidney effects in male rats which are not considered relevant to humans

Remarks: Contains n-Hexane, CAS # 110-54-3., Peripheral nervous system: repeated exposure causes peripheral neuropathy in animals.

### Aspiration toxicity

**Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### Further information

**Product:**

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Remarks: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks: Contains Toluene, CAS # 108-88-3., Prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.

Remarks: Contains Toluene, CAS # 108-88-3., Abuse of vapours has been associated with organ damage and death.

Remarks: Contains Benzene, CAS # 71-43-2., May cause MDS (Myelodysplastic Syndrome).

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

### Summary on evaluation of the CMR properties

Germ cell mutagenicity-  
Assessment : Category 1B

Carcinogenicity -  
Assessment : Category 1B

Reproductive toxicity -  
Assessment : This product does not meet the criteria for classification in categories 1A/1B.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Basis for assessment : Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### **Product:**

Toxicity to fish (Acute toxicity) : Remarks: Expected to be toxic:  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to crustacean (Acute toxicity) : Remarks: Expected to be toxic:  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Expected to be toxic:  
LL/EL/IL50 > 1 <= 10 mg/l

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

- Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL expected to be > 1.0 - <= 10 mg/l
- Toxicity to crustacean (Chronic toxicity) : Remarks: NOEC/NOEL expected to be > 1.0 - <= 10 mg/l
- Toxicity to microorganisms (Acute toxicity) : Remarks: Expected to be harmful: LL/EL/IL50 >10 <= 100 mg/l

### 12.2 Persistence and degradability

#### Product:

- Biodegradability : Remarks: Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment., The volatile constituents will oxidize rapidly by photochemical reactions in air.

Remarks: While biodegradation of Methyl tertiary butyl ether has been documented, it is generally less biodegradable than many petroleum hydrocarbons and has a potential to migrate relatively longer distances in groundwater.

### 12.3 Bioaccumulative potential

#### Product:

- Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

Remarks: Log Kow > =4

- Partition coefficient: n-octanol/water : log Pow: 2 - 7

### 12.4 Mobility in soil

#### Product:

- Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate groundwater., Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment., Contains volatile components., Floats on water.  
Remarks: Methyl tertiary butyl ether degradation may result in the formation of tert-butyl alcohol (TBA).

### 12.5 Results of PBT and vPvB assessment

#### Product:

- Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

### 12.6 Other adverse effects

#### Product:



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Additional ecological information

: Films formed on water may affect oxygen transfer and damage organisms.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose into the environment, in drains or in water courses  
Do not dispose of tank water bottoms by allowing them to drain into the ground.  
This will result in soil and groundwater contamination.

Contaminated packaging

: Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard.  
Do not puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Do not pollute the soil, water or environment with the waste container.

Local legislation  
Remarks

: Local regulations may be more stringent than regional or national requirements and must be complied with.  
Disposal should be in accordance with applicable regional, national, and local laws and regulations.

EU Waste Disposal Code (EWC):  
13 07 02 petrol.

The number given to waste is associated with the appropriate usage. The user must decide if their particular use results in another waste code being assigned.

---

### SECTION 14: Transport information

#### 14.1 UN number

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

**ADN** : 1203  
**ADR** : 1203  
**RID** : 1203  
**IMDG** : 1203  
**IATA** : 1203

### 14.2 Proper shipping name

**ADN** : GASOLINE  
**ADR** : GASOLINE  
**RID** : GASOLINE  
**IMDG** : GASOLINE  
**IATA** : GASOLINE

### 14.3 Transport hazard class

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : F1  
Labels : 3 (N2, CMR, F)  
CDNI Inland Water Waste : NST 3211 Gasoline  
Agreement  
**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
**IMDG**  
Packing group : II  
Labels : 3  
**IATA**  
Packing group : II  
Labels : 3

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : yes  
**ADR**  
Environmentally hazardous : yes  
**RID**  
Environmentally hazardous : yes

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable  
Ship type : Not applicable  
Product name : Not applicable  
Special precautions : Not applicable

**Additional Information** : MARPOL Annex 1 rules apply for bulk shipments by sea.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class (Germany) : WGK 3 highly water endangering  
Remarks: Classification according VwVwS, Annex 2.

Other regulations : Product is subject to the Seveso II directive, Annex I, Number 13.1.  
20. BImSchV applicable  
  
Compliance with Maternity Protection Act paragraphs 4 and 5  
Product is subject to Vorgaben der Betriebs-Sicherheits-Verordnung (BetrSichV).  
Compliance with paragraph 22 of Youth Employment Law.

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment was performed for all substances of this product.

---

## SECTION 16: Other information

**REGULATION (EC) No 1272/2008**  
Flammable liquids, Category 1, H224  
Skin corrosion/irritation, Category 2, H315  
Aspiration hazard, Category 1, H304

Reproductive toxicity, Category 2, H361

### Classification procedure:

On basis of test data.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Germ cell mutagenicity, Category 1B, H340	Expert judgement and weight of evidence determination.
Carcinogenicity, Category 1B, H350	Expert judgement and weight of evidence determination.
Specific target organ toxicity - single exposure, Category 3, H336	Expert judgement and weight of evidence determination.
Chronic aquatic toxicity, Category 2, H411	Expert judgement and weight of evidence determination.

### Full text of R-Phrases

R11	Highly flammable.
R12	Extremely flammable.
R22	Harmful if swallowed.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

### Full text of H-Statements

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Flam. Liq.	Flammable liquids
Muta.	Germ cell mutagenicity
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

ACGIH = American Conference of Governmental Industrial Hygienists  
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
AICS = Australian Inventory of Chemical Substances  
ASTM = American Society for Testing and Materials  
BEL = Biological exposure limits  
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes  
CAS = Chemical Abstracts Service  
CEFIC = European Chemical Industry Council  
CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HP = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

### Further information

Other information : This product is intended for use in closed systems only.

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance- Industrial

#### Uses - Worker

Title : Use as an intermediate- Industrial

#### Uses - Worker

Title : Distribution of substance- Industrial

#### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures- Industrial

#### Uses - Worker

Title : Use as a fuel- Industrial

#### Uses - Worker

Title : Use as a fuel- Professional

#### Uses - Worker

Title : Manufacture of substance- Industrial

#### Uses - Worker

Title : Use as an intermediate- Industrial

#### Uses - Worker

Title : Distribution of substance- Industrial

#### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures- Industrial

#### Uses - Worker

Title : Use as a fuel- Industrial

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Uses - Worker

Title : Use as a fuel- Professional

### Identified Uses according to the Use Descriptor System

#### Uses - Consumer

Title : Use as a fuel  
- Consumer

#### Uses - Consumer

Title : Use as a fuel  
- Consumer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000006</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Continuous process	Handle substance within a closed system.
General exposures (closed systems)Batch process	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,87E+07
Fraction of Regional tonnage used locally:	0,03
Annual site tonnage (tonnes/year):	6,0E+05
Maximum daily site tonnage (kg/day):	2,0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99,0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99,1
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	80,4
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99,1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2,0E+06
Assumed domestic sewage treatment plant flow (m3/d)	10.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE</b>
------------------	--

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>
<b>Section 4.2 -Environment</b>
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000007</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC6a, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,21E+06
Fraction of Regional tonnage used locally:	6,8E-03
Annual site tonnage (tonnes/year):	1,5E+04
Maximum daily site tonnage (kg/day):	5,0E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	92,9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	7,8E+04
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE</b>
------------------	--

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>
<b>Section 4.2 -Environment</b>
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000008</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<p><b>Sector of Use:</b> SU 3</p> <p><b>Process Categories:</b> PROC 15, PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b</p> <p><b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C, ERC 6D, ERC7, ESVOC SpERC 1.1b.v1</p>
<b>Scope of process</b>	Bulk loading (including marine vessel/barge, rail/road car and IBC loading) of substance within closed or contained systems, including incidental exposures during its sampling, storage, unloading, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Process sampling	Sample via a closed loop or other system to avoid exposure
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk closed loading and unloading.	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,87E+07
Fraction of Regional tonnage used locally:	2,0E-03
Annual site tonnage (tonnes/year):	3,75E+04
Maximum daily site tonnage (kg/day):	1,2E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	12
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,1E+06
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>	
<b>Section 4.2 - Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000009</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures-Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU 10 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation of the substance and its mixtures in batch or continuous operations within closed or contained systems, including incidental exposures during storage, materials transfers, mixing, maintenance, sampling and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Process sampling	Sample via a closed loop or other system to avoid exposure
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Store substance within a closed system. Ensure operation is undertaken outdoors.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,65E+07
Fraction of Regional tonnage used locally:	1,8E-03
Annual site tonnage (tonnes/year):	3,0E+04
Maximum daily site tonnage (kg/day):	1,0E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	56,5
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	94,7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,0E+05
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.  
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.  
Risk Management Measures are based on qualitative risk characterisation.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000010</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Refuelling aircraft.	Ensure material transfers are under containment or extract ventilation.
General exposures (closed systems)	Handle substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment cleaning and maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,4E+06
Fraction of Regional tonnage used locally:	1

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Annual site tonnage (tonnes/year):	1,4E+06
Maximum daily site tonnage (kg/day):	4,6E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99,4
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	76,9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4,6E+06
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.  
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.  
Risk Management Measures are based on qualitative risk characterisation.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000011</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Ensure operatives are trained to minimise exposures.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,19E+06
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	5,9E+02
Maximum daily site tonnage (kg/day):	1,6E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	3,4
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,5E+04
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>	
<b>Section 4.2 -Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>	

## SAFETY DATA SHEET

Regulation 1907/2006/EC

**Shell FuelSave Super 95**

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

**Exposure Scenario - Worker**

<b>300000000006</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Continuous process	Handle substance within a closed system.
General exposures (closed systems)Batch process	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,87E+07
Fraction of Regional tonnage used locally:	0,03
Annual site tonnage (tonnes/year):	6,0E+05
Maximum daily site tonnage (kg/day):	2,0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99,0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99,1
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	80,4
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99,1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2,0E+06
Assumed domestic sewage treatment plant flow (m3/d)	10.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE</b>
------------------	--

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>

<b>Section 4.2 -Environment</b>
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000007</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU8, SU9 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC6a, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	2,21E+06
Fraction of Regional tonnage used locally:	6,8E-03
Annual site tonnage (tonnes/year):	1,5E+04
Maximum daily site tonnage (kg/day):	5,0E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	3,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	92,9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	7,8E+04
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE</b>
------------------	--

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>

<b>Section 4.2 -Environment</b>
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000008</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<p><b>Sector of Use:</b> SU 3</p> <p><b>Process Categories:</b> PROC 15, PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b</p> <p><b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C, ERC 6D, ERC7, ESVOC SpERC 1.1b.v1</p>
<b>Scope of process</b>	Bulk loading (including marine vessel/barge, rail/road car and IBC loading) of substance within closed or contained systems, including incidental exposures during its sampling, storage, unloading, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Process sampling	Sample via a closed loop or other system to avoid exposure
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk closed loading and unloading.	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,87E+07
Fraction of Regional tonnage used locally:	2,0E-03
Annual site tonnage (tonnes/year):	3,75E+04
Maximum daily site tonnage (kg/day):	1,2E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	12
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,1E+06
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>	
<b>Section 4.2 - Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000009</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures-Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3, SU 10 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation of the substance and its mixtures in batch or continuous operations within closed or contained systems, including incidental exposures during storage, materials transfers, mixing, maintenance, sampling and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	<p>exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.</p>
General exposures (closed systems)with sample collection	<p>Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.</p>
General exposures (closed systems)Outdoor	<p>Handle substance within a closed system.</p>
Process sampling	<p>Sample via a closed loop or other system to avoid exposure</p>
Laboratory activities	<p>Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.</p>
Bulk transfers	<p>Ensure material transfers are under containment or extract ventilation.</p>
Drum/batch transfers	<p>Ensure material transfers are under containment or extract ventilation.</p>
Equipment cleaning and maintenance	<p>Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.</p>
Storage.	<p>Store substance within a closed system. Ensure operation is undertaken outdoors.</p>

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,65E+07
Fraction of Regional tonnage used locally:	1,8E-03
Annual site tonnage (tonnes/year):	3,0E+04
Maximum daily site tonnage (kg/day):	1,0E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2,0E-03
Release fraction to soil from process (initial release prior to RMM):	1,0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	56,5
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	94,7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,0E+05
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.  
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.  
Risk Management Measures are based on qualitative risk characterisation.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Worker

<b>300000000010</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Refuelling aircraft.	Ensure material transfers are under containment or extract ventilation.
General exposures (closed systems)	Handle substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment cleaning and maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,4E+06
Fraction of Regional tonnage used locally:	1

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Annual site tonnage (tonnes/year):	1,4E+06
Maximum daily site tonnage (kg/day):	4,6E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2,5E-03
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99,4
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	76,9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4,6E+06
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.  
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.  
Risk Management Measures are based on qualitative risk characterisation.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET

Regulation 1907/2006/EC

**Shell FuelSave Super 95**

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

**Exposure Scenario - Worker**

<b>300000000011</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	

<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures;

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Ensure operatives are trained to minimise exposures.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,19E+06
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	5,9E+02
Maximum daily site tonnage (kg/day):	1,6E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	3,4
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,5E+04
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p>	
<b>Section 4.2 -Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org">http://cefic.org</a>).</p>	

SAFETY DATA SHEET

Regulation 1907/2006/EC

**Shell FuelSave Super 95**

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

**Exposure Scenario - Consumer**

<b>300000000208</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 21 <b>Product Categories:</b> PC13 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
<b>Scope of process</b>	Covers consumer uses of automotive fuels only.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 Pa
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentrations up to 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	37.500
covers skin contact area (cm2):	420
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
covers use up to (times/day of use):	0,143
Covers use up to (hours/event):	2
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise.	
Covers use at ambient temperatures.	
Covers use in room size of 20m3	
Covers use under typical household ventilation.	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 210,00 cm2
	For each use event, covers amount up to 37.500 g
	Covers outdoor use.



# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	Covers use in room size of 100 m3
	Covers exposure up to 0,05 hours/event
Fuels Liquid Scooter Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 210,00 cm2
	For each use event, covers amount up to 3.750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0,03 hours/event
Fuels Liquid, Garden Equipment - Use.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 2,00 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 420,00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,03 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,39E+07
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	7,0E+03
Maximum daily site tonnage (kg/day):	1,9E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Conditions and Measures related to municipal sewage treatment plant</b>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,8E+05
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

### Exposure Scenario - Consumer

<b>300000000208</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 21 <b>Product Categories:</b> PC13 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
<b>Scope of process</b>	Covers consumer uses of automotive fuels only.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
------------------	--

<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 Pa
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentrations up to 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	37.500
covers skin contact area (cm2):	420
<b>Frequency and Duration of Use</b>	
Unless stated otherwise.	
covers use up to (times/day of use):	0,143
Covers use up to (hours/event):	2
<b>Other Operational Conditions affecting Exposure</b>	
Unless stated otherwise.	
Covers use at ambient temperatures.	
Covers use in room size of 20m3	
Covers use under typical household ventilation.	

<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 210,00 cm2
	For each use event, covers amount up to 37.500 g
	Covers outdoor use.

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

	Covers use in room size of 100 m3
	Covers exposure up to 0,05 hours/event
Fuels Liquid Scooter Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 210,00 cm2
	For each use event, covers amount up to 3.750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0,03 hours/event
Fuels Liquid, Garden Equipment - Use.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 2,00 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to 420,00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0,03 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0,1
Regional use tonnage (tonnes/year):	1,39E+07
Fraction of Regional tonnage used locally:	5,0E-04
Annual site tonnage (tonnes/year):	7,0E+03
Maximum daily site tonnage (kg/day):	1,9E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1,0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1,0E-05
Release fraction to soil from process (initial release prior to RMM):	1,0E-05
<b>Conditions and Measures related to municipal sewage treatment plant</b>	

# SAFETY DATA SHEET

Regulation 1907/2006/EC

## Shell FuelSave Super 95

Version 3.3

Revision Date 09.03.2015

Print Date 10.03.2015

Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95,5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1,8E+05
Assumed domestic sewage treatment plant flow (m3/d)	2.000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	